

BZ-2 – Magnesia Stabilized Zirconia

MATERIAL TECHNICAL DATA SHEET

TRADE NAME: BZ-2

MATERIAL DESCRIPTION

Chemical Name & Formula: Magnesia Partially Stabilized Zirconia (MgO PSZ) – ZrO₂ + MgO

MAIN COMPONENTS

ZrO₂: 97% MgO: 3%

PHYSICAL DATA

Physical Form: Polycrystalline structure

Boiling Temperature:

M.A.

Melt Temperature:

Vapour Pressure:

Evaporation Rate:

Specific gravity:

N.A.

N.A.

N.A.

Density: 5,65g/cm³
Water solubility: Insoluble
Colour: Yellow
Odour: None

MECHANICAL PROPERTIES AT ROOM TEMPERATURE

Water Absorption	%	0
Vickers Hardness	(HV 0,5)	1200
Flexural Strength	MPa	450
Compressive Strength	MPa	1900
Young's Modulus	GPa	200
Maximum service temperature	°C	850
Thermal Conductivity @20°C	W/(m·K)	2
Thermal Expansion Coefficient (RT-800°C)	10 ⁻⁶ /°C	11
Thermal Shock Resistance (ΔT)	°C	180

PHYSICAL AND CHEMICAL PROPERTIES

Excellent chemical and wear resistance. High mechanical loads with low tendency tol weld. Low resistance to HF (Hydrofluoric acid).

Please, note that all values quoted are based on test pieces and may vary according to component design. These values are not guaranteed in any way and should only be treated as indicative values. They should be used for guidance only and for no other purpose.



Via Industriale, 11 I - 23804 - Monte Marenzo (LC) - ITALY Tel. +39 0341 63.15.88 - E-mail: box@bettini.srl